
NOTES:

- BACKFILL TRENCH PER SPECIFICATIONS OR ROAD OPENING PERMIT.
- SERVICE SADDLES SHALL BE REQUIRED FOR SERVICES THAT ARE 1-1/2" AND 2" DIAMETER.
- METER PIT SHALL NOT BE LOCATED IN TRAFFIC AREAS. IF DRIVEWAY LOCATION IS UNAVOIDABLE SLAB TYPE CAST IRON FRAME AND COVER (CAMPBELL PATTERN NUMBER 1716) SET IN 30" X 30" X 4" THICK 3,800 PSI CONCRETE SHALL BE USED. A HOLE MUST BE CUT IN LID FOR AMR.

MATERIALS:

- 1. CORPORATION STOP: MUELLER MODEL B-25008N;
- 2. CURB STOP: MUELLER MODEL H-15209N;
- CURB BOX: BINGHAM AND TAYLOR CO., FIGURE 4901, COMPLETE WITH OLD STYLE LID;
- 4. SERVICE SADDLE: MUELLER SADDLE SERIES DR2S;
- METER PIT: MUELLER THERMAL COIL METER BOX 3/4" SERVICE: 250CS1842CCBSN 1" SERVICE: 330CS1842CCBSN;
- INSULATING PAD: MUELLER 4" THICK CLOSED CELL POLYETHYLENE FOAM
- 7. TEMPORARY SPACER: SCH 80 PVC, NSF APPROVED
- B. OR EQUALS



STANDARD_DETAILS
COPPER SERVICE

DESIGNED BY:PAD
DRAWN BY:PAD
CHECKED BY:SA
CHECKED BY:SA
CHECKED BY:SA

SCALE NTS

DATE: SHEET NO 1/16/2023 1/1